



Foam Fabricating, Inc

313 Circle of Progress Drive, Suite 200
Pottstown, PA 19464

Ph: (484) 624-4547 • Fax: (484) 624-4548
Toll Free: 1-877-823-1059

On the web: www.jkfoamfab.com



AASHTO Bearing Pads AASHTO-M-251

Description:

Neoprene Bearing Pads provide a uniform transfer of load from beam to structure. They permit rotation at the bearing point due to deflection or misalignment. They absorb vibration and prevent sound transfer, while reducing the destructive action of vibration between movable and stationary members. They also provide for movement caused by normal expansion and contraction.

Neoprene Bearing Pads are used extensively in bridge structures and prestressed and precast concrete buildings. Also used in industrial machinery and heavy equipment applications.

Meets Standard Specifications for Highway Bridges, Fourteenth Edition 1989, Division II, Section 25-Elastomeric Bearings, and AASHTO Standard Specifications for Transportation Materials and Methods of Sampling and Testing, Seventeenth Edition, M251.

Note: Some states specify requirements other than standard AASHTO specifications. When ordering, identify all requirements or submit individual state specification.

Elastomer	Neoprene
Color	Black
Durometer (Shore A)	55-65
Typical Tensile PSI (Minimum)	2500 (2250)
Finish	Smooth
Ultimate Elongation (% Min.)	350
Temperature Range	-40°F - +200°F